



ProLite TH4264MIS-B1

ProLite TH4264MIS a 42" Full HD professional large format display with touch screen functionality

Incorporating the new InfraRed 6 point touch feature along with our supreme panel colour performance, this display offers the optimum performance for a truly multi-user interactive display experience. With the ability to handle up to 6 individual touch points, the TH4264MIS offers an exceptional capacity within Retail, Education, Training, Corporate and B2B markets. Features include PIP and PBP perfect for Video Conferencing or handing multi-input content in many environments. Landscape and Portrait friendly, the display can be mounted according to the application for true impact in Interactive Digital Signage and with Protection Glass the display can handle harshest environments from the Classroom to Public Domain Retail installation

DISPLAY CHARACTERISTICS

Diagonal	42"; 106.5 cm
Touchtechnology	infrared, multitouch (6 compatible touch points - HID, supported only under Windows® 7/8), activated by finger or pen
Panel	IPS, LED-Backlit
Display area h x w	522 x 927.9 mm; 20.6" x 36.5 "
Response time	9 ms
Static contrast	1 000 : 1 with touch panel
Brightness	360 cd/m² with touch panel
Viewing zone	horizontal/vertical: 178°/ 178°; right/left: 89°/ 89°; up/down: 89°/ 89°
Display colour	16.7 million
Pixel pitch h x v	0.4833 x 0.4833 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	30 - 83 KHz
Vertical sync	50 - 85 Hz
Synchronization	Separate Sync
Aspect ratio	16:9
Light transmittance	88%
Max. non-stop operating time	18 hours/day (IRFM on)

POWER MANAGEMENT

EU ENERGY EFFICIENCY LABEL

Energy efficiency class	С
On Mode Power Consumption	103.7W
Annual Energy Consumption	151 kW/annum*
Visible Screen Diagonal	107 cm; 42"

This is information under Regulation (EU) No 1062/2010.

*Based on the power consumption of the television operating 4 hours per day for 365 days. The actual energy consumption will depend on how the television is used.

DIMENSIONS / WEIGHT

Dimensions w x h x d	980.5 x 570 x 123.5 mm
144 1 1 1	00.1
Weight	22 kg

INTERFACES / CONNECTORS / CONTROLLERS

VGA, RCA (VIDEO), S-Video, BNC jack, mini jack
DVI-D, HDMI, DisplayPort
yes
mini jack, RCA L/R(2x)
RS232C, RCA (L/R), VGA (D-Sub), BNC jack (VIDEO)
RS232C, RCA (L/R), mini jack, BNC jack, S-Video, USB (for touch connectivity), RJ45 (for LAN control)

SPECIAL FEATURES

Plug & Play	VESA DDC2B™
Controls	On-Screen-Display in 7 languages (EN, FR, ES, NL, DE, PL, RU) controlled by back controls or a remote control
User controls	picture (picture mode, backlight, contrast, brightness, chroma, phase, sharpness, colour temp., noise reduction, film mode, rest), sound (sound mode, treble, bass, balance, surround, speaker, audio source, reset), screen (PAP setting, display wall, aspect, adjust screen, freeze, touch feature), setting (language, schedule, power save, control setting, network settings, set monitor ID, HDMI control, advanced, information, reset all)
Speakers	2 x 12 W (Stereo)
Safety	CE, TÜV-Bauart, CB, CU
VESA mounting	400 x 200 mm
Colour	Black
Remote control	yes
Orientation	portrait/landscape

ACCESORIES

Driver multi-touch: Windows® 7/8, Android (limited support), Linux (HID compliant), single-touch: Vista, XP, Mac Included accessories power cable, VGA signal cable, DVI-D signal cable, USB cable, remote control, touch pen, iiyama logo sticker, quick start guide, safety guide

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.